

Lakeland ARC-X® Premium Quality

POLYURETHANE FR/ARC RATED RAINWEAR

ANSI Certified • ASTM Arc and Flash Fire Rated for Electric and Gas Applications



AJPU10LY

AJPU10OR

PU offers Superior Performance:

More Comfortable

- Cooler: Breathes and releases perspiration
- Softer and more flexible than other rainwear fabrics
- Lighter weight

More Durable for Longer Wear Cycle

- Softness and pliability make it less prone to get caught on branches and brushes and not tear
- Superior puncture, tear and abrasion resistance
- Reinforced HF sealed seams for maximum strength
- Innovative DRP™ Diamond Reinforced Patch to prevent crotch "blow out"
- Saves money in the long run

ARC X PU Rain Jacket
AJPU10LY - Lime Yellow
AJPU10OR - Orange

- Oversized hood
- D-ring pass through
- Vented back
- Hand warmer pockets

Sizes: Small- 6X

Tall Sizing Available

Arc Rating: 16.3 cal/cm²

Ebtas: 21.9 cal/cm²

HAF: 84%

MVTR: 546 G/M²/24H

Total % body burn: 19.67%

3rd Degree Burn: 6.55%

ANSI 107-2015, Type R, Class 3

ASTM F1891 Arc Flash

ASTM F2733 Flash Fire

ASTM F903 Chemical Resistance

Features Designed to Keep You Dry!



All seams are stitched and high-frequency sealed



Over-size jacket hood with adjustable draw string fits comfortably over a hard hat



Jacket collar with self-storing hood storage



Front storm flap with hook and loop closure



Vented jacket back



Reinforced lanyard opening



3" internal anti-wicking dam on bottom of jacket and pants to prevent internal moisture migration



Two oversize lower front pockets with hook and loop closure and pull tabs, plus hand warmer openings.



Hook and loop adjustable jacket cuffs for optimal fit and comfort





ABPU10LYZ

ABPU10ORZ



Non-metallic quick release bib pant strap clips



One reinforced oversize 9" x 9.5" pant pocket with hook and loop closure and pull tabs



Leg zipper for easy donning and doffing over boots and work shoes.

ARC X PU Bib Style Rain Pant
ABPU10LYZ - Lime Yellow
ABPU10ORZ - Orange

- Cargo Pocket
- Non-metallic, quick release clips
- 16 inch zippered boot openings
- 2 snap fly
- Anti-wicking dam

Arc Rating: 16.3 cal/cm²
Ebtas: 21.9 cal/cm²
HAF: 84%
MVTR: 546 G/M²/24H
Total % body burn: 19.67%
3rd Degree Burn: 6.55%
 ANSI 107-2015, Class E
 ASTM F1891 Arc Flash
 ASTM F2733 Flash Fire
 ASTM F903 Chemical Resistance
Sizes: Small- 6X
Tall Sizing Available

