

- Second generation Pyrolon® Plus 2 offers wet or dry strength superior to that provided by other traditional Flame Resistant disposables
- Meets the NFPA 2113 2020 edition requirements for section 5.1.10.
- · ANSI/ISEA 203 Certified
- Pyrolon® Plus 2 is breathable, making this a cool and comfortable garment to wear.

Pyrolon® Plus 2 can be used in work environments where hazardous or non-hazardous contaminants may be present.

Pyrolon® Plus 2 is certified to the ANSI/ISEA 203-2018 American National Standard for Secondary Single-Use Flame Resistant Protective Clothing for Use Over Primary Flame Resistant Protective Clothing.

## **Pyrolon® Plus 2 Physical Properties**

Physical Property	Test Method	Units	Test Results
Basis Weight	ASTM D3776	oz./sq. yd	2.4 oz/y <sup>2</sup>
Grab Tensile MD	ASTM D5034	lbs.	31.0 lbs.
Grab Tensile XD	ASTM D5034	lbs.	20.0 lbs.
Trapezoidal Tear MD	ASTM D5733	lbs.	4.5 lbs.
Trapezoidal Tear CD	ASTM D5733	lbs.	5.6 lbs.
Air Permeability	ASTM D737	cfm	52 cfm
Char Length MD	ASTM D6413	inches	3.70 inches
Char Length XD	ASTM D6413	inches	3.70 inches
Ignition Point	-	degrees F	1000° F
Surface Resistance	EN1149	Ω	Pass

## **Pyrolon® Plus 2 Configurations**



Coverall 7412B

· Zipper closure Sizes: S - 5XCase Pack: 25



Coverall 7414B

- Zipper closure
- Attached hood
- Boots Elastic wrists

Sizes: S - 5X Case Pack: 25



Coverall 7417B

- Zipper closure Elastic wrists
- · Elastic ankles

Sizes: S - 5XCase Pack: 25



Coverall 7428B


- · Zipper closure
- Attached hood Elastic wrists
- Elastic ankles Sizes: S - 5XCase Pack: 25



Labcoat 7101B


- Snap closure
- 2 pockets
- Long sleeve Sizes: S - 5X

Case Pack: 30



Hood 7713B

- Elastic face
- Covers shoulders
- One size Case Pack: 250



**Boot Cover** 7903BP

- Elastic top
- 17" high

Sizes: S/M, L/XL, 2X Case Pack: 200 pair